

J. LARSON	JULY 17, 2018	
DRAWN BY:	DATE:	REVISED BY:
J. LARSON	JULY 17, 2018	J. LARSON
CHECKED BY:	DATE:	APPROVED BY:




DATE:



LATRINE DETAILS GOLD CREEK FISHING ACCESS SITE FWP #7163618






NOTES:

1. CONCRETE FOR NEW RAMP IS A 3/4" MINUS; 6-1/2 SACK MIX WITH A MINIMUM 28 DAY COMPRESSIVE STRENGTH OF 4000 PSI, REINFORCED WITH #4 BARS @ 12" SPACING BOTH DIRECTIONS.

2. SCREED CONCRETE FOLLOWED BY GROOVING THE SURFACE.

3. SAW CUT CONTRACTION JOINTS AFTER THE RAMP IS GROOVED.




GROOVE DEPTH - 3/4"

NOTE:
1. MFW&P WILL PROVIDE GROOVING TOOL.

SLAB CONTROL JOINT DETAIL

CAST-IN-PLACE CONCRETE BOAT RAMP

PLAN VIEW



NOTES:

1. CONTINUE THICKENED EDGE FOOTING AROUND ENTIRE PERIMETER OF CAST—IN-PLACE CONCRETE.

2. EXTEND AND EXPOXY #4 BARS MIN 20° (12° O.C.) IN EXISTING CONCRETE CONNECTIONS. PROVIDE EXPANSION JOINT MATERIAL ALONG COLD JOINT CONNECTIONS.

3. NO CHAMFER ALONG SIDEWALK/BULKHEAD/EXISTING CONCRETE CONNECTIONS.

4. PROVIDE 3° CLEAR FOR ALL REBAR REINFORCEMENT FROM CONCRETE SURFACES IN CONTACT WITH EARTH. PROVIDE 2° CLEAR FROM ALL OTHER CONCRETE SURFACES.




JULY 17, 2018
DATE:
JULY 17, 2018
DATE:

1/2"RADIUS-

— (1.5" DEPTH)

SECTION A-A'

REVISED BY: DATE: J. LARSON JULY 17, 2018 APPROVED BY: DATE:




NO SCALE



CAST-IN-PLACE BOAT RAMP GOLD CREEK FISHING ACCESS SITE FWP #7163618





J. LARSON	JULY 17, 2018
DRAWN BY:	DATE:
J. LARSON	JULY 17, 2018
CHECKED BY:	DATE:

REVISED BY: DATE:

J. LARSON JULY 17, 2018


APPROVED BY: DATE:


APPROVED BY: DATE:



PUSH-IN BOAT RAMP DETAILS
GOLD CREEK FISHING ACCESS SITE
FWP #7163618







TIMBER STEPS
NO SCALE



J. LARSON	JULY 17, 2018
DRAWN BY:	DATE:
J. LARSON	JULY 17, 2018
CHECKED BY:	DATE:


REVISED BY:	DATE:	
J. LARSON	JULY 17, 2018	
APPROVED BY:	DATE:	





TIMBER STEP DETAILS
GOLD CREEK FISHING ACCESS SITE
FWP #7163618





NOTE:

1. ENDS OF OVERLAPPING SECTIONS
OF FABRIC SHALL BE WRAPPED
AROUND SHARED FENCE POSTS
UNTIL SECURE. - 2"x 2"x 32" WOOD STAKES, 10.0' SPACING ON CENTER SILT FENCE FABRIC,
GRAB TENSILE STRENGTH: 90 LBS (ASTM D1682)
MULLEN BURST STRENGTH: 190 PSI (ASTM D3786)
SLURRY FLOW RATE: 0.3 GAL/MIN/FT MAXIMUM
EQUIVALENT OPENING SIZE: 40-80 (US STD. SEIVE CW-02215)
ULTRAVIOLET RADIATION STABILITY: 90% MINIMUM (ASTM-G-26) NOTE:

1. EITHER SILT FENCE OR FIBER
ROLL MAY BE USED AT THE
CONTRACTORS OPTION. SILT FENCE

-8" STRAW WATTLE 18" WOOD STAKES AT 48"-MAX SPACING 2"-4" EMBEDMENT

FIBER ROLL

## **EROSION CONTROL BARRIER DETAILS**


NO SCALE



<b>BOAT RAMP AREA EROSION CONTROL PL</b>	_AN	
NO SCALE		

J. LARSON	JULY 17, 2018	ı
DRAWN BY:	DATE:	- I
J. LARSON	JULY 17, 2018	
CHECKED BY:	DATE:	1

REVISED BY:	DATE:
J. LARSON	JULY 17, 2018
APPROVED BY:	DATE:





EROSION CONTROL DETAILS GOLD CREEK FISHING ACCESS SITE FWP #7163618

